



NOTES: 1) MINIMUM CABLE LENGTH MEASURED FROM STRAIN RELIEF TO CONNECTOR MATING SURFACE.
 2) TOTAL LEADWIRE CONNECTION 1314mm MINIMUM FROM POSITIVE STRAIN RELIEF TO NEGATIVE STRAIN RELIEF OF ADJACENT MODULE.

CONFIDENTIAL			
INFORMATION CONTAINED HEREIN CONSTITUTES PROPRIETARY CONFIDENTIAL INFORMATION OF FIRST SOLAR AND IS ACCEPTED ONLY SUBJECT TO THAT UNDERSTANDING. IT IS TO BE KEPT CONFIDENTIAL & NOT COPIED, REPRODUCED, USED OR CONVEYED TO OTHERS WITHOUT FIRST SOLAR'S WRITTEN AUTHORIZATION. THIS MATERIAL SHALL REMAIN THE PROPERTY OF FIRST SOLAR AND IT IS TO RETURNED UPON DEMAND.			
UNLESS OTHERWISE SPECIFIED BREAK ALL SHARP EDGES DIMENSIONS ARE IN MILLIMETERS TOLERANCES PER ISO 2768-mK		 First Solar, Inc PERRYSBURG, OHIO	
		TITLE FS-Series 4 PV Module	
		DRAWN: TCT CAD FILE: PRD-027-A.idw	
		CHK'D: APM DRAWING NO.	
		DATE: 3/13/2014 PRD-027-A	
		SCALE: 1:6 SHT. 1 OF 1 SIZE B	

REV	DATE	BY	DESCRIPTION
A	6/21/2017	APM	CLARIFIED CABLE LENGTH, ADDED NOTE, WAS A-SIZE