



Series 7 FT1.

505-540 Watt Thin Film Solar Module

Series 7 FT1 thin film solar modules combine First Solar's thin film technology with an optimized structural design to deliver improved efficiency, enhanced installation velocity, and unmatched lifetime energy performance for large/utility-scale PV projects.



More Lifetime Energy per Nameplate Watt

- Industry's best (0.3%) annual degradation rate
- Warranted to retain >90.8% power output after 25 years
- Superior temperature coefficient, spectral and shading response



Unmatched Quality and Reliability

- End-to-end manufacturing process for globally consistent quality
- Tested and certified to IEC standards and beyond
- Durable glass/glass construction
- Immune to and warranted against power loss from cell cracking
- 25-year Linear Performance Warranty
- 10-year Limited Product Warranty



Optimized Module Design

- Optimized back rail mount design enhances installation velocity
- Frameless design improves soiling and snow shedding
- Dual junction box design reduces wire management complexity and cost



Industry's Most Eco-efficient PV Solution

- Industry leading carbon footprint, water footprint and energy payback time
- Globally available PV module recycling services



Domestically Manufactured

- Manufactured in India, for the Indian market

19.3%

HIGH BIN EFFICIENCY

25YR

LINEAR PERFORMANCE WARRANTY

98%


WARRANTY START POINT

0.3%

WARRANTED ANNUAL DEGRADATION RATE

First Solar Lifetime Energy Advantage

From 25 Year Warranted Annual Power Degradation



Learn more about First Solar
and Series 7 FT1
at firstsolar.com/S7

Series 7 FT1.

Electrical Specifications

MODEL TYPES: FS-7XXXA-FT1 (XXX = NOMINAL POWER)

RATINGS AT STANDARD TEST CONDITIONS (1000W/m², AM 1.5, 25°C)²

Nominal Power ³ (-0/+5%)	P _{MAX} (W)	505	510	515	520	525	530	535	540
Efficiency (%)	%	18.1	18.3	18.4	18.6	18.8	19.0	19.1	19.3
Cell Efficiency (%)	%	18.9	19.1	19.3	19.5	19.7	19.9	20.1	20.3
Voltage at P _{MAX}	V _{MAX} (V)	182.5	183.4	184.3	185.2	186.0	186.9	187.8	188.7
Current at P _{MAX}	I _{MAX} (A)	2.77	2.78	2.80	2.81	2.82	2.84	2.85	2.86
Open Circuit Voltage	V _{OC} (V)	223.9	224.5	225.0	225.6	226.1	226.7	227.2	227.7
Short Circuit Current	I _{SC} (A)	3.01	3.02	3.03	3.04	3.04	3.05	3.06	3.06
Maximum System Voltage	V _{SYS} (V)	1500 ⁵							
Limiting Reverse Current	I _R (A)	5.0							
Maximum Series Fuse	I _{CF} (A)	5.0							


RATINGS AT NOMINAL OPERATING CELL TEMPERATURE OF 45°C (800W/m², 20°C air temperature, AM 1.5, 1m/s wind speed)²

Normal Power	P _{MAX} (W)	378.1	381.8	385.6	389.4	393.2	396.8	400.6	404.4
Voltage at P _{MAX}	V _{MAX} (V)	168.8	169.7	170.6	170.8	171.7	172.5	173.4	174.3
Current at P _{MAX}	I _{MAX} (A)	2.24	2.25	2.26	2.28	2.29	2.30	2.31	2.32
Open Circuit Voltage	V _{OC} (V)	211.9	212.4	212.9	213.5	214.0	214.5	215.0	215.5
Short Circuit Current	I _{SC} (A)	2.44	2.44	2.45	2.45	2.46	2.47	2.47	2.48

TEMPERATURE CHARACTERISTICS

Module Operating Temperature Range	(°C)	-40 to +85
Temperature Coefficient of P _{MAX}	T _K (P _{MAX})	-0.32%/°C [Temperature Range: 25°C to 75°C]
Temperature Coefficient of V _{OC}	T _K (V _{OC})	-0.28%/°C
Temperature Coefficient of I _{SC}	T _K (I _{SC})	+0.04%/°C

Mechanical Specifications



PACKAGING INFORMATION

Model Type	Modules Per Pack	Packs per 12m 15T Container
FS-7XXXA-FT1	48	8

MECHANICAL DESCRIPTION

Length	2300mm
Width	1216mm
Area	2.80m ²
Module Weight	36.8kg
Leadwire ⁶	2.5mm ² , 500mm (+) & Bulkhead (-)
Connectors	TE Connectivity PV4-S or alternate
Junction Box	IP68 Rated
Bypass Diode	N/A
Cell Type	Thin film CdTe semiconductor, up to 268 cells
Frame Material	Galvanized steel
Front Glass	Heat strengthened
Back Glass	Heat strengthened
Encapsulation	Laminate material with edge seal
Frame to Glass Adhesive	Silicone
Load Rating	2400Pa

Install in portrait only

- Limited power output and product warranties subject to warranty terms and conditions
- All ratings ±10%, unless specified otherwise. Specifications are subject to change
- Measurement uncertainty applies
- Testing Certifications/Listings pending
- IEC 61730-1: 2016 Class II
- Leadwire length from junction box exit to connector mating surface

Certifications & Tests⁴

CERTIFICATIONS & LISTINGS

UL 61730 1500V Listed
IEC 61215:2021 & 61730-1:2016⁵
IEC 61701 Salt Mist Corrosion
IEC 60068-2-68 Dust and Sand Resistance
BIS

EXTENDED DURABILITY TESTS

IEC TS 63209-1 Extended Stress Test
Long-Term Sequential
Thresher Test
PID Resistant

QUALITY & EHS

ISO 9001:2015
ISO 14001:2015
ISO 45001:2018
ISO 14064-3:2006
EPEAT Silver Registered



LEADING THE WORLD'S
SUSTAINABLE ENERGY FUTURE

First Solar

Disclaimer

All images shown are provided for illustrative purposes only and may not be an exact representation of the product. First Solar, Inc. reserves the right to change product images at any time without notice. The information included in this Module Datasheet is subject to change without notice and is provided for informational purposes only. No contractual rights are established or should be inferred because of user's reliance on the information contained in this Module Datasheet. Please refer to the appropriate Module User Guide and Module Product Specification document for more detailed technical information regarding module performance, installation and use.

First Solar, the First Solar logo, and Leading the World's Sustainable Energy Future are trademarks of First Solar, Inc., registered in the U.S. and other countries. Series 7 and FT1 are trademarks of First Solar, Inc.